


HUNTING ARROW SIZE SELECTION

| COMPOUND BOW with Release Aid 301-340 FPS ATA RATING | HUNTING ARROW CUT LENGTH | | | | | | | | | | | | TRADITIONAL | |
|--|-------------------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|--------------|
| | 23" | 24" | 25" | 26" | 27" | 28" | 29" | 30" | 31" | 32" | 33" | 34" | RECURVE | LONGBOW |
| BOW POUNDAGE | RECOMMENDED SHAFT SPINE RANGE | | | | | | | | | | | | BOW POUNDAGE | |
| 22-26 | | | | 700-600 | 700-600 | 600-500 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 24-28 | |
| 27-31 | | | 700-600 | 700-600 | 600-500 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 29-32 | |
| 32-36 | | 700-600 | 700-600 | 600-500 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 33-36 | 12-16 |
| 37-41 | 700-600 | 700-600 | 600-500 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 37-41 | 17-21 |
| 42-46 | 700-600 | 600-500 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 42-46 | 22-26 |
| 47-51 | 600-500 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 47-51 | 27-31 |
| 52-56 | 600-500 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 52-56 | 32-36 |
| 57-61 | 500-400 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 300-250 | 57-61 | 37-41 |
| 62-66 | 500-400 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 300-250 | 250-200 | 62-66 | 42-46 |
| 67-72 | 500-400 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 300-250 | 250-200 | 250-200 | 67-72 | 47-52 |
| 73-78 | 400-350 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 300-250 | 250-200 | 250-200 | 250-200 | 73-78 | 53-58 |
| 79-84 | 400-350 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 300-250 | 250-200 | 250-200 | 250-200 | 200-150 | 79-84 | 59-64 |
| 85-90 | 400-350 | 350-300 | 350-300 | 350-300 | 300-250 | 300-250 | 300-250 | 250-200 | 250-200 | 250-200 | 200-150 | 200-150 | 85-90 | 65-70 |

NOTE: For fractional arrow lengths round up or down to the closest column. Example: If arrow length is 28.25" round down to 28" column. If arrow length is 28.5" round up to 29" column.



ADJUST THE CHART TO YOUR BOW SET-UP

Chart uses a 301-340 FPS ATA bow speed rating, screw-in 100 grain points, and release aid. Make the following adjustments to your bow point and weight if your set-up is different.

Setup Variables—Add/Subtract from Actual Bow Weight

Compound Bow Speed Rating

Up to 300 FPS = -5 lbs of Bow Weight
301-340 FPS = No Adjustment
341-350 FPS = +5 lbs of Bow Weight
351 FPS or Higher = +10 lbs of Bow Weight

Compound Release Type

Mechanical Release = No Adjustment
Finger Release = +5 lbs of Bow Weight

Inserts/Outserts

<25 Grains = No Adjustment
>25 Grains = +3 lbs of Bow Weight per 25 Grains of Point Weight >100 Grains

Points

Points <100 Grains = -3 lbs of Bow Weight per 25 Grains of Point Weight <100 Grains
Points = 100 Grains = No Adjustment
Points >100 Grains = +3 lbs of Bow Weight per 25 Grains of Point Weight >100 Grains



FREE

GET THE EASTON ARCHERY APP

- Arrow Spine Selector
- F.O.C. & Kinetic Energy Calculators
- Hunting & Target Video Library
- Complete Arrow & Component Info
- ASA 3D Scoring Utility



SCAN TO DOWNLOAD

